

JetFlex® FL is a 13 oz. quality, economical choice for an all around outstanding front-lit banner or billboard material for UV, solvent or screen-printing. Both strong and durable, JetFlex FL prints vibrantly and consistently and is tear and fade resistant. Available in both matte and gloss finishes in widths ranging from 30" - 80". In widths 98" and above, this product is called Normandy® Pro FL.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN 53830	1100 x 1100 dtex	1000 x 1000 denier
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	440 g/m <sup>2</sup>	13 oz/yd <sup>2</sup>
Tensile Strength	ASTM D 751:2006, C.R.E	1501 X 128 kgF	333 X 281 lbs/in
Tear Strength (warp/weft)	ASTM D 4830:1988, C.R.E	15 X 10 kgF	39 X 21 lbs/in
Flame Resistance	DIN 4102	NFPA701, CA Fire Marshall, NYC (MEA)	
Low Temperature (No Crack at:)	ASTM D 2137	Low at -40°C	Low at -40°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Fungus Resistant	ASTM G21	Treated	

### Applications

	Backlit	Banner	Billboard	Blockout	Building Wrap	Display Systems	Truckside
Applications		■	■			■	

### Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	□	■	■		

### Available Sizes

Metric (m)	English (inches)
0.76, 0.965, 1.37, 1.60, 1.83, 2.03	30, 38, 54, 63, 72, 80

**Key:** ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)